



Illumination unit with filter disc



Stage and objectives

LAB LINE MET

The metallurgical reflected light microscope for material testing and surface testing, as well as quality assurance in industry



www.atestor.hu

Features

- The KERN OKM is an excellent metallurgical reflected light microscope, e.g. for surface quality testing of raw materials and finished products in industry
- The strong, continuously dimmable 30 W halogen reflected illumination unit (Philips) ensures excellent, high-contrast images
- The illumination unit with an integrated 5-slot filter wheel for blue, green, yellow, grey and blank means that you can quickly change the colour filter for different contrast views
- A large mechanical stage for reflected illumination applications is configured as standard. The coarse and fine focusing knob on both sides guarantees optimal adjustment and focusing of your sample
- A simple polarising unit (analyser and polariser) is included with delivery
- A large selection of different eyepieces, objectives and a polarising unit are also available
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-mount adapter is required to connect a camera to the trinocular version. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

Scope of application

- Metallurgy, material testing, quality assurance

Applications/Samples

- Opaque and thick samples, workpieces (surfaces, fold lines, coatings)

Technical data

- Infinity optical system
- Quadplex nosepiece
- Siedentopf 30° inclined/360° rotatable
- Diopter adjustment: One-sided
- Overall dimensions W×D×H 440×200×460 mm
- Net weight basic configuration approx. 8 kg

STANDARD



Model	Standard configuration					Price excl. of VAT ex works €
	Tube	Eyepiece	Objective quality	Objectives	Illumination	
KERN OKM 173	Trinocular	HWF 10×/ø 18 mm	Infinity Plan	5×/10×/LWD 20×/LWD40×	30 W Halogen (incident)	1890,-

Model outfit		Model KERN	Order number	Price/piece excl. of VAT ex works €
		OKM 173		
Eyepieces (23,2 mm)	HWF 10×/∅ 18 mm	✓	OBB-A1403	45,-
	HWF 10×/∅ 18 mm (reticule 0,1 mm) (non-adjustable)	✓	OBB-A1349	60,-
	WF 5×/∅ 20 mm	○	OBB-A1355	55,-
	WF 12,5×/∅ 14 mm	○	OBB-A1353	75,-
	WF 16×/∅ 13 mm	○	OBB-A1354	45,-
Infinity Plan achromatic objectives	5×/0,11 W.D. 6,80 mm	✓	OBB-A1268	105,-
	10×/0,25 W.D. 4,3 mm	✓	OBB-A1244	195,-
	20×/0,40 (spring-loaded) W.D. 2,14 mm	○	OBB-A1251	265,-
	40×/0,65 (spring-loaded) W.D. 0,45 mm	○	OBB-A1258	290,-
Infinity Plan achromatic objectives for long working distance	20×/0,40 W.D. 8,35 mm	✓	OBB-A1252	290,-
	40×/0,65 W.D. 3,90 mm	✓	OBB-A1259	405,-
	50×/0,70 (spring-loaded) W.D. 1,95 mm	○	OBB-A1266	450,-
	80×/0,80 (spring-loaded) W.D. 0,85 mm	○	OBB-A1271	500,-
Trinocular tube	<ul style="list-style-type: none"> • Siedentopf 30° inclined/360° rotatable • Interpupillary distance 50 – 75 mm • Light distribution 80:20 • Diopter adjustment: One-sided 	✓	OBB-A1346	
Mechanical stage	<ul style="list-style-type: none"> • Stage size W×D 200×140 mm • Travel 76×52 mm • Coaxial coarse and fine focusing knobs 	✓		
Illumination	30 W Halogen spare bulb (incident)	✓	OBB-A1372	35,-
Reflected illumination unit	5-filter unit (Blue, Green, Yellow, Grey, Empty)	✓		
	Polarising unit (Incl. analyser and polariser slide)	✓		
C-Mount	1×	○	OBB-A1514	120,-
	0,5× (focus adjustable)	○	OBB-A1515	185,-

✓ = Included with delivery

○ = Option